

(b) Each davit, winch, fall, and other launching-appliance must be thoroughly inspected at least once a year, and repaired as needed.

(c) Each item of survival equipment with an expiration date must be replaced during the annual inspection and repair if this date has passed.

(d) Each battery used in an item of survival equipment and clearly marked with an expiration date must be replaced during the annual inspection and repair if this date has passed.

(e) Except a storage battery used in a lifeboat or in a rescue boat, each battery used in an item of survival equipment and not clearly marked with an expiration date must be replaced during the annual inspection and repair.

(f) Compliance with the requirements of this section does not relieve the master or person in charge of the duty of compliance with requirements in § 131.540(a) of this subpart to keep the equipment ready for immediate use when the vessel is under way.

**§ 131.580 Servicing of inflatable life-rafts, inflatable lifejackets, inflatable buoyant apparatus, and inflated rescue boats.**

(a) An inflatable liferaft or inflatable buoyant apparatus must be serviced at a facility specifically approved by the Commandant for the particular brand, and in accordance with servicing procedures meeting the requirements of part 160, subpart 160.151, of this chapter—

(1) No later than the month and year on its servicing sticker affixed under 46 CFR 160.151–57(n), except that servicing may be delayed until the next scheduled inspection of the vessel, provided that the delay does not exceed 5 months; and

(2) Whenever the container is damaged or the container straps or seals are broken.

(b) Each inflatable lifejacket and hybrid inflatable lifejacket or work vest must be serviced:

(1) Within 12 months of its initial packing; and

(2) Within 12 months of each subsequent servicing, except that servicing may be delayed until the next scheduled inspection of the OSV, provided that the delay does not exceed 5 months.

(c) Each inflatable lifejacket must be serviced in compliance with subpart 160.176 of this chapter.

(d) Each hybrid inflatable lifejacket or work vest must be serviced in accordance with the manual provided under § 160.077–29 of this chapter.

(e) Repair and maintenance of inflatable rescue boats must follow the manufacturers' instructions. Each repair, except an emergency repair made aboard the vessel, must be made at a servicing facility approved by the Commandant (CG–ENG).

[CGD 82–004 and CGD 86–074, 62 FR 49340, Sept. 19, 1997, as amended by USCG–2002–11118, 67 FR 58541, Sept. 17, 2002; USCG–2009–0702, 74 FR 49235, Sept. 25, 2009; USCG–2012–0832, 77 FR 59782, Oct. 1, 2012]

**§ 131.585 Periodic servicing of hydrostatic-release units.**

(a) Except a disposable hydrostatic-release unit with an expiration date, each hydrostatic-release unit must be serviced—

(1) Within 12 months of its manufacture and within 12 months of each subsequent servicing, except when a servicing due after 12 months is delayed not more than 5 months until the next scheduled inspection of the vessel; and

(2) In compliance with subpart 160.062 of this chapter.

(b) The springs of each spring-tensioned gripe used with a hydrostatic-release unit must be renewed when the unit is serviced and tested.

**§ 131.590 Firefighting equipment.**

(a) The master shall ensure that the vessel's required firefighting equipment is on board in the prescribed location and always ready for use, other than when the equipment is being serviced.

(b) The master shall, at least once each 12 months, ensure the performance of the tests and inspections of each portable fire extinguisher, semiportable fire extinguisher, and fixed fire-extinguishing system aboard described by Table 132.350 of this subchapter.

(c) The master shall keep records of these tests and inspections, showing the dates of their performance, the number or other identification of each unit undergoing them, and the name of